

Notes:

DL: 100T (metric)
 Wrapped angle: As indicated on drawing
 SWL = DL/(0,75*DAF)
 DAF: min. 1,3
 TD: -20°C

MBL: 4:1

Connection: 52x M36 grade 8.8, 2280 Nm
 - Pretension: 415 Nm

Design and manufacturing in accordance with:


DNV - Standard for certification - No 2.22 - Lifting appliances

Pad eyes are for lifting of the Lead block only
 Use 4-legged sling set with shackles WLL 2 t EN 13889
 Load factor applied: 2

Weight: 3270 kg.


A	26.08.11	Issued for construction	GM	JAV	
1	05.09.11	Added dimension	GM	JAV	
0	26.08.11	Issued for comments	GM	JAV	
Rev:	Date	Note	drw. by	chk	Appr.

Item	Qty	Description	Designation	Material	Mass
12	2	Eye bolt - DIN 580 - M8 - A4			0,1 kg
11	4	Screw - ISO 4017 - M12x65 - A4			0,1 kg
10	4	Washer - ISO 7089 - M12 - A4			0 kg
9	1	Wire holder	00702-0		30,1 kg
8	1	Lubricating Nipple - DIN 71412 A AM10x1 - A4			0 kg
7	12	Washer - Nord-Lock 20sp			0 kg
6	12	Screw - ISO 4017 - M20x70 - GR. 8.8 - HDG			0,2 kg
5	1	Axle holder - with locking face	00717-0		20,3 kg
4	1	Axle holder	00703-0		20,7 kg
3	1	Axle	00704-0		181,1 kg
2	1	Sheave - W - W - 1314x1570/440	00661-0		1231,4 kg
1	1	Block house	00701-A		1772,7 kg



Longhammerveien 7
5536 Haugesund - Norway

post@gleipnir.no
www.gleipnir.no

Projection:  Tol. prin: ISO 8015 Gen. Tol.: ISO 2768-1m Geom. tol: ISO 1101

Sheet size: A2 Scale: 1:15 Repl. for: Repl. by:

Title: **Lead Block - V - W - PCD 1314**
for ø73mm wire
DL 100T (metric)

Drwg. No.: 00700-RT Rev.: A

Reference: Sheet: 1 of 1

This drawing is the property of Gleipnir AS. It is not to be used, reproduced or disclosed in whole or in part for any purpose without the written permission of Gleipnir AS.