



A (1:5)



B (1:5)



Notes:
 Standards applied:
 DNV "standard for certification No. 2.22"
 NS 3472
 EN 1993-1-8
 Machine directive
 NORSOK R-CR-002
 Surface conservation:
 NORSOK M501 system 1
 Design factors:
 DAF: 1,3
 Load factor: 1,3

Item	Qty	Description	Designation	Material	Mass
15	2	Shackle super - bow - with safety bolt - GP - WLL 175 T	X00022	Gr. 8	158,2 kg
14	4	Lubrication Nipple - DIN 71412 A - M10x1 - A4	X00017	A4	0 kg
13	12	Bolt - DIN 933 - M24x50 - A480	X00016	A4-80	0,3 kg
12	12	Washer - Nord-lock - NL24ss - A4	X00015	A4	0 kg
11	2	Axle holder - disc - 240x290x20	00066	W 1.4418	7,5 kg
10	1	Pin bearing - 240x421	00067	W 1.4418	145,4 kg
9	2	Thrust washer - 240x330/19	00065	Comp	0,8 kg
8	1	Bearing journal radial - 240x280x150	00064	CuAl10Ni	21,5 kg
7	1	Sheave - wire - ø1330 x PCD 1232 x 190 x 77	00056	S355 J2+N	663,5 kg
6	2	Bearing journal - radial - SBT 240x245/40	X00013	Comp	0,1 kg
5	1	Nut - M160x6 - DL 1750 kN	00061	S355 J2+N	56,3 kg
4	1	Eye round DL 1750 kN	00060	S355 J2+N	140,4 kg
3	4	Bolt - DIN 6912 - M12x30 - HDG	X00021	Gr. 8.8	0 kg
2	1	Bearing journal - axial - 285x160/20	00063	CuAl10Ni	7,2 kg
1	1	Block house	00057A	S355 J2+N	1106,1 kg

Total weight: Approx 2500 kg

Rev	Date	Text	Team	Kontr.	Godtkt.
A	17.09.09	Dim. added.	SW	JAV	
0	10.08.09	Issued for construction	SW	JAV	

Longhammervien 7
 5536 Haugesund - Norway
 post@gleipnir.no
 www.gleipnir.no

Projection: Gen. Tol.: NS-ISO 2768-1m Gen. Weld.: NS-EN 287-1 / 288 Gen. Roughness:
 Sheet size: A2 Scale: 1:15 Repl. for: Repl. by:
 Title: Block - Reeve - DL 1750 kN in Eye for ø77mm wire
 Dwg. No.: 00073A Rev.: A
 Reference: Sheet: 1 of 1

This document and all information contained herein are the confidential and proprietary assets of GLEIPNIR AS. No part may be reproduced or transmitted in any form or by any means without the written permission of GLEIPNIR AS.