



A-A (1 : 10)

Connection: 20x M24 bolts grade 8.8 - Torque: 665 kN

0	06.01.09	Issued for Construction	SW	JAV	
Revi	Dato	Tekst	Tegn.	Kontr.	Godk.

Total weight: 655 kg

Item	Qty	Description	Designation	Material	Mass
11	1	Lubricating Nipple M10x1	DIN 71412A	A4	0 kg
10	2	Hex Nut M24	DIN 934	Gr. 8	0,1 kg
9	2	Hex Bolt M24 x 220	DIN 931	Gr. 8.8	0,9 kg
8	4	Nord-Lock washer M24	NL24	ST	0 kg
7	2	Tube	90-0023	PA 6-G	0,2 kg
6	4	Hex bolt M20 x 35	DIN 933	Gr. 8.8	0,2 kg
5	4	Nord-Lock washer M20	NL20	ST	0 kg
4	2	Axle holder ø150 pin	16-0002	S355 J2G3	0,8 kg
3	1	Bearing pin ø150 x 170	11-0013	S355 J2G3	31,2 kg
2	1	Custom sheave ø950 x PCD 864 x 130	09-0004-48	ST	216,9 kg
1	1	Vertical lead block house	71-0004	S355 J2G3	399,5 kg

	Projection:	Gen. Tol.: NS-ISO 2768-1m	Gen. Weld.: NS-EN 287-1 / 288	Gen. Roughness:
	Sheet size: A3	Scale: 1:10	Repl. for:	Repl. by:
Title: Vertical Lead block				
Wire pull 50 T / Wrapped angle 90 DGR				
Drwg. No.: 2120-0004			Rev.: 0	
Reference: 781-0010			Sheet: 1 of 1	

Longhammveien 7
 5536 Haugesund - Norway
 post@gleipnr.no
 www.gleipnr.no